

enviro prime SB

Solvent Based Primer



Date: Jan 09
Issue: 3

Description

Enviro Prime SB is a 1-Part solvent based primer. It provides excellent adhesion for most of the Enviro range of systems.

Advantages

- Simple to use primer
- Suitable for a wide range of substrates
- Versatile

Uses

Enviro Prime SB is suitable for use with the following range of Enviro Systems:

- Enviro Clad
- Enviro 700PUR
- Enviro 500PUR

Application Directions

Substrate Preparation

The surface must be clean, and free from all loose particles, including dust, laitance, grease, coatings, curing compounds or any other foreign matter.

Where boards are used, these are to be fixed according to the manufacturers instructions and are to be fit for purpose.

Apply suitable and approved joint caulking material such as Enviro Seal PUR and allow to cure before application of Enviro Prime SB, to all joints and cracks greater than 2mm.

Application

Enviro Prime SB can be applied using brush or roller. Apply one coat of Enviro Prime SB at a rate of 5 – 8m² per litre to the prepared substrate. Allow to dry before proceeding with topcoats.

Estimating Data (Theoretical)

The consumption of Enviro Prime SB will depend upon substrate condition and type.

As a guide: One 4 ltr of Enviro Prime SB will cover approximately 20 – 32m² based on one coat at rate of 5 – 8m² per litre.

Packaging

Enviro Prime SB is supplied in, 15 ltr, 4 ltr and 1 ltr pails.

Curing

Enviro Prime SB generally can be recoated after 1 hour depending on the weather.

Shelf Life

Enviro Prime SB should be removed from all tools and equipment, prior to hardening with Enviro Thinners No.1 or Thinners No.7. Cured material can only be mechanically removed.

Safety Advice

Enviro Prime SB contents are flammable. Keep away from naked flame. In the event of fire extinguish with foam or CO₂. Always provide adequate ventilation and wear appropriate personal protection equipment (PPE) during use. Avoid breathing vapours. Avoid contact with skin. If swallowed, DO NOT induce vomiting, give glass of water and seek immediate medical advice. If contact with skin, wash off splashes of material with clean water and soap. If irritation occurs seek immediate medical advice. Refer to MSDS.

KEEP OUT OF REACH OF CHILDREN.



Manufactured by Waterproofing Technologies Pty Ltd

Address: 295 Princes Highway St Peters NSW 2044 Sydney Australia

Telephone: +61 2 8595 8699

Facsimile: +61 2 8595 8660

Web: www.envirosystems.com.au

Statement of Responsibility

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, his representative or the contractor is responsible for checking the suitability of products for their intended use.

Note:

Field service where provided, does not constitute supervisory responsibility. Suggestions made by Enviro Systems either verbally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Enviro Systems are responsible for carrying out procedures appropriate to a specific application.