

# DUROTREAD

## External foot trafficable membrane

**DUROTREAD** is a modified **DUROCOAT AC** membrane with fine grade aggregate which provides a non-slip textured surface for deck and other exposed areas.

### USE AREAS

- Foot trafficable roof decks
- Balconies and decks with or without tiling

### PRINCIPLE CHARACTERISTICS

- Single component
- Non-toxic, water clean up.
- Permanently flexible
- Seamless
- Environmentally safe
- UV stable— excellent for external use
- Fungal and algae resistant
- Easily maintained
- Low odour
- Solids Content 58%

### COLOUR

- Grey
- Other colours on request

### PACKAGING

- 20 Litre

### APPLICATION

**Priming:** Apply **DUROPRIME WBE** as a primer and allowed to dry prior to application of **DUROTREAD**.

Apply **DUROTREAD** by roller or brush at a rate of 2 - 4 Ltr /m<sup>2</sup> per coat. Apply in one direction only to provide even texture and finish. Two coat application required to achieve a dry film thickness of minimum 0.50 mm.



**Durotech Industries** 14 Essex Street, P.O Box 5092, Minto, NSW 2566  
**Telephone: +61 2 9603 1177 Fax: +61 2 9603 3796**  
 Email: sales@durotechindustries.com.au Web: www.durotechindustries.com.au



*The information provided in this technical bulletin is as correct in detail as possible and is intended to give a fair description of the product and its capabilities. In practice, the substrate and environmental conditions vary widely, making it essential for the user to determine the products suitability for a particular application and that the product is not used beyond its physical limitations. The product is guaranteed providing that it is applied in accordance with the manufacturer's instructions as stated in this data sheet and any relevant Standard or Code and provided that the building and installation is structurally sound. Durotech terms and conditions of sale apply.*